



Space-Saving Folding Rail

An industry first, automatic fold design eliminates obstructions at the bottom of the stairway. (optional)



Features & Benefits

- Just 10.5" wide folded—the industry's narrowest
- Patented helical worm drive is smooth and energy-efficient
- DC drive even runs during power interruptions
- Clean installation and maintenance.
- Patented Folding Rail option eliminates obstruction at stair base (optional)
- Powerful enough to travel up to a 52° incline
- Includes 2 wireless remotes
- ETL Listed - 3148125, Commercially rated



The energy-efficient patented worm drive requires no greases or lubricants.



Safety sensors on carriage and platform stop the lift instantly at obstacles.

The World's Most Compact Stair Lift

Engineered to the highest industry standards, Pinnacle stair lifts are designed for optimal comfort, convenience and aesthetics. Space-saving Pinnacle folds to 10.5 inches, making it the narrowest lift on the market. And its patented helical worm gear drive generates the smoothest, safest and most energy-efficient ride available.

| Specifications | SL600 |
|--|---|
| Maximum Weight Capacity: | 350 lbs. (160 kg) |
| Overspeed Governor: | Standard, Commercially Rated |
| Track (rail) Type: | Clear Anodized Aluminum |
| Travel: | 16' Standard; 70' Maximum (21 m) |
| Average Number of Return Trips per Charge: | Up to 60 |
| Control in Armrest: | Yes (left or right hand operation) |
| Lift Mounts to Steps or Wall: | Steps |
| Minimum Folded Width: | 10.5" (26.7 cm); 13" with Folding Rail |
| Minimum Footrest Height: | 3.5" (8.9 cm) |
| Clear Distance Between Armrests: | 19" (48.3 cm) |
| Floor to Seat Height Low / High: | 20" / 24.5" (50.8 / 62 cm) |
| Minimum Wall to Stair Side of Rail: | 6" (15.25 cm); 8.5" with folding rail |
| Seat Depth: | 16" (40.6 cm) |
| Backrest Height From Top of Seat: | 18" (45.7 cm) |
| Electrical Requirements: | 120–240 VAC |
| Operation Power: | 24V DC Battery |
| Speed: | 20 fpm |
| Incline Range: | 32 - 52° |
| Drive System: | Helical Worm Gear |
| Folding Rail Option: | Automatic and Mechanical |
| Safety Design: | Complies with ASME A18.1, CAN/CSA B44.1, ASME A17.5 |
| Safety Devices: | Centrifugal Overspeed Brake Bi-directional Footrest Obstruction Sensor Swivel Seat Cut-off Switch Final Limits / Seat Belt Chassis Obstruction Switching Optional Key Switch |
| Warranty: | 3-Year on Components 10-Year on gear rack 1-Year on Batteries |